

JACKET N

uncoated multi-purpose Polyester Jacket

Quality made in Germany

Special Hoses



Construction

Jacket 100 % polyester high tenacity yarn, circular woven
warp threads 2-ply or 3-ply twisted
Twill or plain weave

Exterior uncoated, natural white

Elongation max change in length 3 % at a load of 1 - 250 kg
max. change in diameter 3 % at an internal pressure
of 1 - 16 bar



Option: Including thread

to assist with the pulling
through of objects

Internal diameter		Flat width*	Weight**	Wall thickness***
mm	inch	mm	g/m	mm
25	1	41	58	1,00
32	1 ¼	53	67	1,00
38	1 ½	60	80	1,00
42		66	88	1,00
45	1 ¾	70	100	1,00
52	2	82	115	1,00
65	2 ½	101	130	1,00
70	2 ¾	110	191	1,00
75	3	118	205	1,00
90	3 ½	141	215	1,00
102	4	159	260	1,00
110	4 ⅓	171	355	1,00
115		176	275	1,00
125	5	194	410	1,00
150	6	237	495	1,00

* tolerance of ± 2mm

** tolerance of ± 10%

*** tolerance of ± 0,3mm

PARSCH

*Schläuche • Armaturen
GmbH & Co. KG*

Gildestraße 16
49477 Ibbenbüren/Germany
Telefon: +49 (0) 5451 9 29-0
Fax: +49 (0) 5451 92 92 92

www.parsch.de
info@parsch.de

Quality made by Parsch

JACKET N

uncoated multi-purpose Polyester Jacket



Characteristics

good abrasion resistance and long service life
external resistance to oil, fuel and chemical products
ageing and ozone resistant – weather resistant
lightweight and flexible – easy to coil
minimum maintenance
cold resistant to $-30\text{ }^{\circ}\text{C}$
heat resistant up to $+80\text{ }^{\circ}\text{C}$

Applications

bundling of cables and wires
as protection hose for chains, belts, ropes, steel
wire ropes or hydraulic hoses
mechanical engineering
building construction
electrical and cable industry
vehicle construction

Supply Lengths

coils up to 100 m
maximum length up to 1.000 m, continuous, lapped


Special Hoses




Standard diameter

mm
25
38
42
52
65
75

other diameter on request



Twill weave



Plain weave

certified according to
DIN EN ISO 9001 : 2008
Quality Management System

Quality made by Parsch